

MINI BALL VALVE

Ball valve

Shut off system

Technical Data Sheet



Description

The Mini ball valve can equip all types of installations from heating systems, home water installations to heavy duty industrial applications at high pressure and temperature.

- Standard passage



MINI BALL VALVE

Ball valve - Shut off system

DN		PFA in bar	Ref.	Weight Kg
"	mm			
1/4	8	10	149B5368	0,06
3/8	10	10	149B5369	0,07
1/2	15	10	149B5370	0,10

Technical features

Operating temperature	0 °C to 90 °C
Permissible operating pressure (PFA) in water	See table above
Connection	Male / female, (BSP)
Mediums	Water and compatible fluids

Nomenclature and materials

Description	Materials	EURO	ANSI
Body	Chromed brass		
Ball	Chrome plated brass		
Seals	PTFE		
Handlever	PA 66 (polyamide)		

Approvals

ACS

International construction Standards :


Thread connection according to NFE 03-005 ISO 228

Application

General process, heating and multi-fluid applications

Sizing

DN	Ø	F	S	H	L
"	mm	mm	mm	mm	mm
1/4	5	8	38,5	24,3	30,5
3/8	8	9	40	26	30
1/2	10	11	45	28	30



MINI BALL VALVE

The descriptions and photographs contained in this product specification sheet are supplied by way of information only and are not binding.

Socla reserves the right to carry out any technical and design improvements to its products without prior notice. Warranty : All sales and contracts for sale are expressly conditioned on the buyer's assent to Socla terms and conditions found on its website at www.socla.com. Socla hereby objects to any term, different from or additional to Socla terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Socla.



A WATTS Brand

Socla sas

365 rue du Lieutenant Putier • 71530 Virey-Le-Grand • France

Tel. +33 03 85 97 42 00 • Fax +33 03 85 97 42 42

contact@wattswater.com • www.socla.com

ISO 9001 version 2015 / ISO 18001